

# **PRODUCT DATA SHEET**

## AXCL GTi2 Motor Engine Oil

### Description

AXCL GTi2 Motor Engine Oil has been specifically formulated to meet high performance requirements of the latest model car and trucks. This product was specially designed for use in sports cars and luxury vehicles that require highly stable engine oil that will withstand the most extreme demanding performance criteria. It is so thoroughly tested that it has been approved by the internationally recognized organization known as the API (American petroleum Institute) and their department called the Eolcs. This product carries the full donut approval for API SM/CF and energy conserving (EC).

#### **Performance Level**

API SM/SL/SJ, MIL-L-46152D, CCMC G5/PD

#### **Benefits & Advantages**

- Improved fuel economy & power output.
- Reduced emissions
- Enhances life of crankcase
- Extended drain capability
- Superior lubrication-increased engine life

#### **Specification & Parameter**

| #   | Test                             | Method      | Result |
|-----|----------------------------------|-------------|--------|
| 1.  | Viscosity Grade                  | SAE         | 20W-50 |
| 2.  | Color                            | Visual      | L 2.50 |
| З.  | Kin. Viscosity @ 40 °C, cSt      | ASTM D 445  | 185    |
| 4.  | Kin. Viscosity @ 100 °C, cSt     | ASTM D 445  | 20.01  |
| 5.  | Viscosity Index                  | ASTM D 2270 | 125    |
| 6.  | Density @ 15 °C                  | ASTM D 1298 | 0.88   |
| 7.  | Foam Test, Sequence II @ 93.5 °C | ASTM D 892  | Pass   |
| 8.  | TBN, mg KOH∕g                    | ASTM D 2896 | 7.5    |
| 9.  | Flash Point, °C                  | ASTM D 92   | 260    |
| 10. | Pour Point, °C                   | ASTM D 97   | - 27   |
| 11. | Sulphated Ash                    | ASTM D 874  | 1.1    |

\*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.

AXCL GTi2 Motor Engine Oil

AXCL LUBES, the AXCL logo and related marks are trademarks of AXCL GULF FZC, used under license.

All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. Data provided is based on standard tests under laboratory conditions and is given as a guide only. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AXCL GULF FZC or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Doc#: AGL/FM/25-0 Page 1 of 1

January 2016