



Research & Development

PRODUCT DATA SHEET

AXCL LOXY Dexron Type A (Automatic Transmission Fluid)

Description

AXCL LOXY DEXRON ATF TYPE A is a universal type transmission fluid for use in automatic gear boxes and power steering boxes where General Motors Type A Fluid is required. It has a high viscosity index, low pour point and special additives to increase oxidation resistance, rust and corrosion protection and anti-wear properties. It is also highly suitable for power steering units in passenger cars and commercial vehicles.

Performance Level

GM Dexron Type A

Benefits & Advantages

- Anti-wear properties
- Compatibility with seal materials
- Protection against deposit formation
- Fluidity over a wide range

Specification & Parameter

#	Test	Method	Result
1.	Viscosity Grade	GM	Type A
2.	Color	Visual	Red
3.	Kin. Viscosity @ 40 °C	ASTM D 445	30.05
4.	Kin. Viscosity @ 100 °C	ASTM D 445	5.20
5.	Viscosity Index	ASTM D 2270	103
6.	Density @ 15 °C	ASTM D 1298	0.871
7.	Flash Point °C	ASTM D 92	≥ 190
8.	Pour Point °C	ASTM D 97	≤ -18
9.	Foam Sequence I, II, III	ASTM D 892	0/0

**Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.*

AXCL Loxy ATF DEX Type A

January 2019

AXCL LUBES, the AXCL logo and related marks are trademarks of AXCL GULF FZC, used under license

All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. Data provided is based on standard tests under laboratory conditions and is given as a guide only. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AXCL GULF FZC or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.