



Research & Development

PRODUCT DATA SHEET

AXCL 2T OUTBOARD MOTOR OIL API TC SAE 30

PRODUCT DESCRIPTION

2T is a superior quality, low ash forming SAE 30 two stroke motor oil. It is dyed blue for ease of use and identification. 2T provides miscibility and fluidity characteristics that meet grade 2 of SAE J 1536 and exceeds the API TC performance level

PERFORMANCE LEVEL

API TC, SAE J1536 GRADE 2, JASO FC

BENEFITS & ADVANTAGES

- Effective lubrication at varying speeds
- Longer spark plug life
- Maintains optimum viscosity at different temperatures
- Meets and exceeds API TC

SPECIFICATION & TECHNICAL PARAMETER

SAE VISOSITY GRADE 30			
1.	Color	Visual	B&C
2.	Kin. Viscosity @ 100 °C	D 445	8.84
3.	Kin. Viscosity @ 40 °C	D 445	62.5
4.	Density @ 60/60F	D 1298	0.878
5.	Viscosity Index	D 2270	116
6.	Pour Point	D 97	≤ -6
7.	Flash Point	D 92	≥ 160
8.	Foam Seq I, II, III	D 892	PASS

**Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.*

***All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative*