



## AXCL Scooter 4T Engine Oil

### Description

AXCL Scooter 4T is a premium 4-Stroke motorcycle engine oil specially designed to give superior protection and performance even under extreme conditions. These oils are specially designed for high temperature operating conditions providing optimum performance even in these tough city driving conditions. These oils provide outstanding oxidation and wear protection for extended oil engine life, minimize engine deposits due to excellent sludge and varnish control. Its anti-wear additive system reduces wear of highly stressed engine and gearbox components under severe operating conditions and improves engine and gearbox durability.

- Superior performance and smooth ride by active prevention of friction
- Superior protection of gears during frequent gear changes
- Prevention of clutch slippage at start up and at varying speeds

### Performance Level

ACEA A3-96/B3-96, API SJ, JASO MA2

### Benefits & Advantages

- Cost effective protection helps resist engine and gearbox wear, contributing to improved engine reliability.
- Detergency and dispersancy additives assist in reducing piston and ring deposits, helping maintain engine power and performance.
- Multifunctional formulation, suitable for motorcycle engine, clutch and gearbox use as well as portable power generation engines requiring API SJ performance.

### Specification & Parameter

#	Test	Method	Result			
			10W40	15W40	20W40	20W50
1.	Viscosity Grade	SAE	10W40	15W40	20W40	20W50
2.	Color	ASTM D 1500	L 2.0	L 2.0	L 2.0	L 2.5
3.	Kin. Viscosity @ 40 °C, cSt	ASTM D 445	105.5	108	118	180
4.	Kin. Viscosity @ 100 °C, cSt	ASTM D 445	14.40	14.50	14	19
5.	Viscosity Index	ASTM D 2270	140	138	118	120
6.	Density @ 15 °C	ASTM D 1298	0.875	0.878	0.885	0.890
7.	Foam Test, Sequence II @ 93.5 °C	ASTM D 892	0/0	0/0	0/0	0/0
8.	TBN, mg KOH/g	ASTM D 2896	7.50	7.50	7.50	7.50
9.	Flash Point, °C	ASTM D 92	222	230	230	242
10.	Pour Point, °C	ASTM D 97	-27	-27	-24	-24



Research & Development

# PRODUCT DATA SHEET

*\*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.*

AXCL GTi Motor Engine Oil

January 2016

AXCL LUBES, the AXCL logo and related marks are trademarks of AXCL GULF FZC, used under license.

All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. Data provided is based on standard tests under laboratory conditions and is given as a guide only. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AXCL GULF FZC or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

AXCL GULF, P O Box 41563