

## AXCL Calcite Guard Xtreme Grease (Calcium Sulphonate)

AXCL Calcium Sulfonate Nano Calcite Grease is a revolutionary calcium sulfonate grease fortified with cutting-edge nanotechnology. This advanced formula surpasses conventional greases, delivering unparalleled performance and protection in the most demanding industrial environments. Nano calcites within the formula form a microscopic shield, significantly reducing wear and tear on machinery components even under the most demanding conditions. AXCL NanoGuard Grease delivers unparalleled performance and protection, ensuring smooth operation, extended equipment life, and reduced maintenance costs for your most critical machinery.

### Key Features

- **Nano Fortified:** Nano calcites within the grease form a microscopic shield, significantly reducing wear and tear on machinery components even under extreme pressures, high operating temperatures (up to 300°C), and constant water exposure.
- **Superior Load Carrying Capacity:** Engineered to handle the heaviest loads and extreme pressures encountered in heavy-duty machinery.
- **Exceptional Anti-Wear and EP Protection:** Minimizes friction and wear, extending equipment life and reducing maintenance costs.
- **Excellent Water Washout and Spray Off Resistance:** The advanced formula adheres tenaciously to surfaces, providing long-lasting lubrication even in wet and harsh environments.
- **Rust and Oxidation Inhibition:** Protects metal surfaces from rust and corrosion, ensuring smooth operation and preventing costly downtime.
- **Environmentally Friendly:** Formulated with responsible ingredients, minimizing environmental impact.

### Benefits & Advantages

- Extended equipment life through superior wear protection
- Reduced maintenance costs due to extended lubrication intervals
- Reliable operation in extreme temperatures, heavy loads, and wet environments
- Enhanced protection against rust and corrosion
- Environmentally conscious choice

### Applications

AXCL Calcium Sulfonate Nano Calcite Grease is ideal for a wide range of heavy-duty machinery operating under severe conditions, including:

- Steel mills, paper mills, sawmills, cement plants
- Mines, rock crushing, metal foundries
- Construction equipment, heavy-duty vehicles
- Electrical motors and conductors exposed to salt, acid, or high moisture environments

## Specification & Parameter

#	Test	Method	Result
1.	Appearance	Visual	Smooth & Homogenous
2.	NLGI Grade	D 217	2
3.	Unworked Penetration @ 25°C	D 217	285
4.	Drop Point, °C	D 556	> 330
5.	Rust testing, Rating	D 1763	Pass
6.	Soap type	-	Calcium Sulfonate Complex
7.	Base Oil Viscosity, cSt	D 128	460
8.	Four Ball Weld load, Kg	D 2783	620
9.	Water Washout, wt %	D 1264	< 2.5
10.	Water Spray Off, %	D 4049	< 15.0
11.	Timken Ok Load, lbs	D 2509	65
12.	Operating Temperature, °C	-	- 30 °C to 300 °C

*\*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.*

AXCL Calcium Sulfonate Nano Calcite Grease

AXCL LUBES, the AXCL logo and related marks are trademarks of AXCL GULF FZC, used under license.

All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. Data provided is based on standard tests under laboratory conditions and is given as a guide only. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AXCL GULF FZC or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

AXCL GULF, P O Box 41563

Sharjah, United Arab Emirates

Telephone: +971 6 5263030

[www.axcllubes.com](http://www.axcllubes.com), [info@axcllubes.com](mailto:info@axcllubes.com)